



Patent Images

▲ Full Text
? Help

Go to Page:

 Go

Sections:

- [Front Page](#)
- [Drawings](#)
- [Specifications](#)
- [Claims](#)

916,889

13

upwardly, and then inwardly from its lower
end to form a horizontal flange, a flange F, a
sleeve adapted to rest upon said flange, said
sleeve being provided with chimney engag-
ing members and there being lugs formed
upon the out-turned flange of the outer wick
tube adapted to concentrically space said
sleeve from said wick tube, a centrally lo-
cated flame spreader, a centrally located
mantle support mounted thereon and spaced
members for supporting the flame spreader
from the upper edge of said sleeve, there
being openings formed through the lower
portion of said sleeve and there being open-
ings formed through the up-turned portion
D of the outer wick tube, said horizontal
flange separating the last named openings
from the opening of the sleeve.
7. In a device of the character described,

the combination with a bowl, of an inner
wick tube and an outer wick tube, a sleeve
adapted to surround the upper end of the
outer wick tube, there being an out-turned
horizontal flange upon the upper end of the
outer wick tube, lugs carried by said flange
adapted to concentrically space said sleeve
from the outer wick tube, there being open-
ings formed through the lower portion of
said sleeve, and an imperforate horizontally
disposed flange upon which said sleeve is
adapted to rest and which closes the bottom
of said sleeve.

In testimony whereof, I affix my signa-
ture, in presence of two witnesses.

BERNARD F. ROEHRIG.

Witnesses:

J. D. MASTER,
H. C. RHOADS.